

预制连接器的Profinet电缆, 4芯, 屏蔽
Profinet cable with prefabricated connector, 4 core, shielded

45C 型

RJ45, IP20插头

RJ45, IP20弯头插头

RJ45, IP67插头



	RPB	RPBR	RPRD
OE 	PN-RPB-OE-45C/L00XX 31034000XX	PN-RPBR-OE-45C/L00XX 31034100XX	PN-RPRD-OE-45C/L00XX 31033000XX
RPB 	PN-RPB-RPB-45C/L00XX 31039500XX	PN-RPBR-RPB-45C/L00XX 31032100XX	PN-RPRD-RPB-45C/L00XX 31031300XX
RPBR 		PN-RPBR-RPBR-45C/L00XX 31032200XX	
RPRD 			PN-RPRD-RPRD-45C/L00XX 31033300XX
MSD 			
MRD 			
FSDBP 	PN-RPB-FSDBP-45C/L00XX 31031900XX		

此页匹配线缆参数



类型: 45C
 护套: PUR
 结构: 22AWG*4C 导体7根束绞
 安装: 适用于活动安装或拖链安装
 温度: -20 °C ... 80 °C

45C 型



M8 针式, 直头

M8 孔式, 直头

M12 针式, 直头



OE

M8MS

M8FS

MSD

PN-M8MS-OE-45C/L00XX
31032300XX

PN-M8FS-OE-45C/L00XX
31033200XX



M8MS

PN-M8MS-M8MS-45C/L00XX
31033400XX

PN-M8FS-M8MS-45C/L00XX
31034300XX

PN-MSD-M8MS-45C/L00XX
31037700XX



RPB

PN-M8MS-RPB-45C/L00XX
31032400XX

PN-M8FS-RPB-45C/L00XX
31034200XX

此页匹配线缆参数



类型: 45C
护套: PUR
结构: 22AWG*4C 导体7根束绞
安装: 适用于活动安装或拖链安装
温度: -20 °C ... 80 °C

订购方式 (长度定制示例)

PN - [] - [] - 45C / L []

接口类型

接口类型

线缆长度

注: 以10厘米为刻度
例: L0010=1米

信号指示、线路分配

M12	RJ45	线芯颜色	信号
1	1	黄色	TD+
3	2	橙色	TD-
2	3	白色	RD+
4	6	蓝色	RD-