


现场总线组件——预制电缆, PROFIBUS DP, M12
Profibus components——Prefabricated cable, PROFIBUS DP, M12



技术参数







额定电压	[V]	总线电缆	250	M12	250
额定电流	[A]		4		4
接触电阻			≤5mΩ		≤5mΩ
信号线横截面	[mm ²]		0.25		0.25
信号线结构			19x0.13mm		19x0.13mm
符合UL94所确定的阻燃等级			V0		V0
电缆直径	[mm]		7.8		7.8
插针/插针表面镀层			CuSn//Ni/Au		CuSn//Ni/Au
插芯材料			PA66		PA66
防护等级			IP65/IP67/IP69K		IP65/IP67/IP69K
温度参数					
电缆, 固定式安装	[°C]		-40 ... 80		-40 ... 80
电缆, 活动式安装	[°C]		-20 ... 80		-20 ... 80
针式/孔式	[°C]		-25 ... 90		-25 ... 90

订货数据

	型号	订货号	型号	订货号
0.3m	DP-OE-OE-8BP/L0003	3321000003	DP-MSB-OE-8BP/L0003	3321100003
0.5m	DP-OE-OE-8BP/L0005	3321000005	DP-MSB-OE-8BP/L0005	3321100005
1m	DP-OE-OE-8BP/L0010	3321000010	DP-MSB-OE-8BP/L0010	3321100010
2m	DP-OE-OE-8BP/L0020	3321000020	DP-MSB-OE-8BP/L0020	3321100020
5m	DP-OE-OE-8BP/L0050	3321000050	DP-MSB-OE-8BP/L0050	3321100050
10m	DP-OE-OE-8BP/L0100	3321000100	DP-MSB-OE-8BP/L0100	3321100100
15m	DP-OE-OE-8BP/L0150	3321000150	DP-MSB-OE-8BP/L0150	3321100150
20m	DP-OE-OE-8BP/L0200	3321000200	DP-MSB-OE-8BP/L0200	3321100200
可订制	DP-OE-OE-8BP/L0000	3321000000	DP-MSB-OE-8BP/L0000	3321100000

信号指示、线路分配

M12	线芯颜色	信号
2	绿色	A电缆
4	红色	B电缆



M12
250
4
≤5mΩ
0.25
19x0.13mm
V0
7.8
CuSn//Ni/Au
PA66
IP65/IP67/IP69K

M12
250
4
≤5mΩ
0.25
19x0.13mm
V0
7.8
CuSn//Ni/Au
PA66
IP65/IP67/IP69K

M12
250
4
≤5mΩ
0.25
19x0.13mm
V0
7.8
CuSn//Ni/Au
PA66
IP65/IP67/IP69K

-40 ... 80
-20 ... 80
-25 ... 90

-40 ... 80
-20 ... 80
-25 ... 90

-40 ... 80
-20 ... 80
-25 ... 90

型号	订货号
DP-MRB-OE-8BP/L0003	3321200003
DP-MRB-OE-8BP/L0005	3321200005
DP-MRB-OE-8BP/L0010	3321200010
DP-MRB-OE-8BP/L0020	3321200020
DP-MRB-OE-8BP/L0050	3321200050
DP-MRB-OE-8BP/L0100	3321200100
DP-MRB-OE-8BP/L0150	3321200150
DP-MRB-OE-8BP/L0200	3321200200
DP-MRB-OE-8BP/L0000	3321200000

型号	订货号
DP-FSB-OE-8BP/L0003	3321300003
DP-FSB-OE-8BP/L0005	3321300005
DP-FSB-OE-8BP/L0010	3321300010
DP-FSB-OE-8BP/L0020	3321300020
DP-FSB-OE-8BP/L0050	3321300050
DP-FSB-OE-8BP/L0100	3321300100
DP-FSB-OE-8BP/L0150	3321300150
DP-FSB-OE-8BP/L0200	3321300200
DP-FSB-OE-8BP/L0000	3321300000





型号	订货号
DP-FRB-OE-8BP/L0003	3321400003
DP-FRB-OE-8BP/L0005	3321400005
DP-FRB-OE-8BP/L0010	3321400010
DP-FRB-OE-8BP/L0020	3321400020
DP-FRB-OE-8BP/L0050	3321400050
DP-FRB-OE-8BP/L0100	3321400100
DP-FRB-OE-8BP/L0150	3321400150
DP-FRB-OE-8BP/L0200	3321400200
DP-FRB-OE-8BP/L0000	3321400000

M12	线芯颜色	信号
2	绿色	A电缆
4	红色	B电缆

M12	线芯颜色	信号
2	绿色	A电缆
4	红色	B电缆

M12	线芯颜色	信号
2	绿色	A电缆
4	红色	B电缆

现场总线组件——预制电缆, PROFIBUS DP, M12
Profibus components——Prefabricated cable, PROFIBUS DP, M12



技术参数





额定电压	[V]	M12	250	M12	250
额定电流	[A]	4	4	4	4
接触电阻		≤5mΩ	≤5mΩ	≤5mΩ	≤5mΩ
信号线横截面	[mm ²]	0.25	0.25	0.25	0.25
信号线结构		19x0.13mm	19x0.13mm	19x0.13mm	19x0.13mm
符合UL94所确定的阻燃等级		V0	V0	V0	V0
电缆直径	[mm]	7.8	7.8	7.8	7.8
插针/插针表面镀层		CuSn//Ni/Au	CuSn//Ni/Au	CuSn//Ni/Au	CuSn//Ni/Au
插芯材料		PA66	PA66	PA66	PA66
防护等级		IP65/IP67/IP69K	IP65/IP67/IP69K	IP65/IP67/IP69K	IP65/IP67/IP69K
温度参数					
电缆, 固定式安装	[°C]	-40 ... 80	-40 ... 80	-40 ... 80	-40 ... 80
电缆, 活动式安装	[°C]	-20 ... 80	-20 ... 80	-20 ... 80	-20 ... 80
针式/孔式	[°C]	-25 ... 90	-25 ... 90	-25 ... 90	-25 ... 90

订货数据

	型号	订货号	型号	订货号
0.3m	DP-MSB-FSB-8BP/L0003	3321130003	DP-MRB-FSB-8BP/L0003	3321230003
0.5m	DP-MSB-FSB-8BP/L0005	3321130005	DP-MRB-FSB-8BP/L0005	3321230005
1m	DP-MSB-FSB-8BP/L0010	3321130010	DP-MRB-FSB-8BP/L0010	3321230010
2m	DP-MSB-FSB-8BP/L0020	3321130020	DP-MRB-FSB-8BP/L0020	3321230020
5m	DP-MSB-FSB-8BP/L0050	3321130050	DP-MRB-FSB-8BP/L0050	3321230050
10m	DP-MSB-FSB-8BP/L0100	3321130100	DP-MRB-FSB-8BP/L0100	3321230100
15m	DP-MSB-FSB-8BP/L0150	3321130150	DP-MRB-FSB-8BP/L0150	3321230150
20m	DP-MSB-FSB-8BP/L0200	3321130200	DP-MRB-FSB-8BP/L0200	3321230200
可订制	DP-MSB-FSB-8BP/L0000	3321130000	DP-MRB-FSB-8BP/L0000	3321230000

信号指示、线路分配

M12	线芯颜色	信号	M12	M12	线芯颜色	信号	M12
2	绿色	A电缆	2	2	绿色	A电缆	2
4	红色	B电缆	4	4	红色	B电缆	4



技术参数

额定电压	[V]	M12	M12
额定电流	[A]	250	250
接触电阻		4	4
信号线横截面	[mm ²]	≤5mΩ	≤5mΩ
信号线结构		0.25	0.25
符合UL94所确定的阻燃等级		19x0.13mm	19x0.13mm
电缆直径	[mm]	V0	V0
插针/插针表面镀层		7.8	7.8
插芯材料		CuSn//Ni//Au	CuSn//Ni//Au
防护等级		PA66	PA66
温度参数		IP65/IP67/IP69K	IP65/IP67/IP69K
电缆, 固定式安装	[°C]		
电缆, 活动式安装	[°C]	-40 ... 80	-40 ... 80
针式/孔式	[°C]	-20 ... 80	-20 ... 80
		-25 ... 90	-25 ... 90

订货数据

	型号	订货号	型号	订货号
0.3m	DP-MSB-FRB-8BP/L0003	3321140003	DP-MRB-FRB-8BP/L0003	3321240003
0.5m	DP-MSB-FRB-8BP/L0005	3321140005	DP-MRB-FRB-8BP/L0005	3321240005
1m	DP-MSB-FRB-8BP/L0010	3321140010	DP-MRB-FRB-8BP/L0010	3321240010
2m	DP-MSB-FRB-8BP/L0020	3321140020	DP-MRB-FRB-8BP/L0020	3321240020
5m	DP-MSB-FRB-8BP/L0050	3321140050	DP-MRB-FRB-8BP/L0050	3321240050
10m	DP-MSB-FRB-8BP/L0100	3321140100	DP-MRB-FRB-8BP/L0100	3321240100
15m	DP-MSB-FRB-8BP/L0150	3321140150	DP-MRB-FRB-8BP/L0150	3321240150
20m	DP-MSB-FRB-8BP/L0200	3321140200	DP-MRB-FRB-8BP/L0200	3321240200
可订制	DP-MSB-FRB-8BP/L0000	3321140000	DP-MRB-FRB-8BP/L0000	3321240000

信号指示、线路分配

M12	线芯颜色	信号	M12	M12	线芯颜色	信号	M12
2	绿色	A电缆	2	2	绿色	A电缆	2
4	红色	B电缆	4	4	红色	B电缆	4