




现场总线组件——预制电缆, PROFIBUS PA, M12不锈钢
Profibus components——Prefabricated cable, PROFIBUS PA, M12 Stainless steel



技术参数




额定电压	[V]	60
额定电流	[A]	4
接触电阻		≤5mΩ
插针材料		CuSn
插针表面材料		Ni/Au
插头材料		TPU,阻燃性高,具自熄灭性质
防护等级		IP65/IP67/IP69K
温度参数		
针式/孔式	[°C]	-25 ... 90

订货数据

	型号	订货号	型号	订货号
0.3m	PA-MSA-OE-8BA/L0003	3329100003	PA-MRA-OE-8BA/L0003	3329200003
0.5m	PA-MSA-OE-8BA/L0005	3329100005	PA-MRA-OE-8BA/L0005	3329200005
1m	PA-MSA-OE-8BA/L0010	3329100010	PA-MRA-OE-8BA/L0010	3329200010
2m	PA-MSA-OE-8BA/L0020	3329100020	PA-MRA-OE-8BA/L0020	3329200020
5m	PA-MSA-OE-8BA/L0050	3329100050	PA-MRA-OE-8BA/L0050	3329200050
10m	PA-MSA-OE-8BA/L0100	3329100100	PA-MRA-OE-8BA/L0100	3329200100
15m	PA-MSA-OE-8BA/L0150	3329100150	PA-MRA-OE-8BA/L0150	3329200150
20m	PA-MSA-OE-8BA/L0200	3329100200	PA-MRA-OE-8BA/L0200	3329200200
可订制	PA-MSA-OE-8BA/L0000	3329100000	PA-MRA-OE-8BA/L0000	3329200000

信号指示、线路分配

M12	线芯颜色	信号	M12	线芯颜色	信号
1	橙色	DATA+	1	橙色	DATA+
2	n.c.		2	n.c.	
3	蓝色	DATA-	3	蓝色	DATA-
4	屏蔽		4	屏蔽	



60
4
≤5mΩ
CuSn
Ni/Au
TPU,阻燃性高,具自熄灭性质
IP65/IP67/IP69K

60
4
≤5mΩ
CuSn
Ni/Au
TPU,阻燃性高,具自熄灭性质
IP65/IP67/IP69K

60
4
≤5mΩ
CuSn
Ni/Au
TPU,阻燃性高,具自熄灭性质
IP65/IP67/IP69K

-25 ... 90

-25 ... 90

-25 ... 90

型号	订货号
PA-FSA-OE-8BA/L0003	3329300003
PA-FSA-OE-8BA/L0005	3329300005
PA-FSA-OE-8BA/L0010	3329300010
PA-FSA-OE-8BA/L0020	3329300020
PA-FSA-OE-8BA/L0050	3329300050
PA-FSA-OE-8BA/L0100	3329300100
PA-FSA-OE-8BA/L0150	3329300150
PA-FSA-OE-8BA/L0200	3329300200
PA-FSA-OE-8BA/L0000	3329300000

型号	订货号
PA-MSA-FSA-8BA/L0003	3329130003
PA-MSA-FSA-8BA/L0005	3329130005
PA-MSA-FSA-8BA/L0010	3329130010
PA-MSA-FSA-8BA/L0020	3329130020
PA-MSA-FSA-8BA/L0050	3329130050
PA-MSA-FSA-8BA/L0100	3329130100
PA-MSA-FSA-8BA/L0150	3329130150
PA-MSA-FSA-8BA/L0200	3329130200
PA-MSA-FSA-8BA/L0000	3329130000



型号	订货号
PA-MRA-FSA-8BA/L0003	3329230003
PA-MRA-FSA-8BA/L0005	3329230005
PA-MRA-FSA-8BA/L0010	3329230010
PA-MRA-FSA-8BA/L0020	3329230020
PA-MRA-FSA-8BA/L0050	3329230050
PA-MRA-FSA-8BA/L0100	3329230100
PA-MRA-FSA-8BA/L0150	3329230150
PA-MRA-FSA-8BA/L0200	3329230200
PA-MRA-FSA-8BA/L0000	3329230000

M12	线芯颜色	信号
1	橙色	DATA+
2	n.c.	
3	蓝色	DATA-
4	屏蔽	

M12	线芯颜色	信号	M12
1	橙色	DATA+	1
2	n.c.		2
3	蓝色	DATA-	3
4	屏蔽		4

M12	线芯颜色	信号	M12
1	橙色	DATA+	1
2	n.c.		2
3	蓝色	DATA-	3
4	屏蔽		4

现场总线组件——预制电缆, PROFIBUS PA, M12不锈钢
Profibus components——Prefabricated cable, PROFIBUS PA, M12 Stainless steel



技术参数


额定电压	[V]	60	60
额定电流	[A]	4	4
接触电阻		≤5mΩ	≤5mΩ
插针材料		CuSn	CuSn
插针表面材料		Ni/Au	Ni/Au
插头材料		TPU,阻燃性高,具自熄灭性质	TPU,阻燃性高,具自熄灭性质
防护等级		IP65/IP67/IP69K	IP65/IP67/IP69K
温度参数			
针式/孔式	[°C]	-25 ... 90	-25 ... 90

订货数据

	型号	订货号	型号	订货号
0.3m	PA-FRA-OE-8BA/L0003	3329400003	PA-MSA-FRA-8BA/L0003	3329140003
0.5m	PA-FRA-OE-8BA/L0005	3329400005	PA-MSA-FRA-8BA/L0005	3329140005
1m	PA-FRA-OE-8BA/L0010	3329400010	PA-MSA-FRA-8BA/L0010	3329140010
2m	PA-FRA-OE-8BA/L0020	3329400020	PA-MSA-FRA-8BA/L0020	3329140020
5m	PA-FRA-OE-8BA/L0050	3329400050	PA-MSA-FRA-8BA/L0050	3329140050
10m	PA-FRA-OE-8BA/L0100	3329400100	PA-MSA-FRA-8BA/L0100	3329140100
15m	PA-FRA-OE-8BA/L0150	3329400150	PA-MSA-FRA-8BA/L0150	3329140150
20m	PA-FRA-OE-8BA/L0200	3329400200	PA-MSA-FRA-8BA/L0200	3329140200
可订制	PA-FRA-OE-8BA/L0000	3329400000	PA-MSA-FRA-8BA/L0000	3329140000

信号指示、线路分配

M12	线芯颜色	信号	M12	线芯颜色	信号	M12
1	橙色	DATA+	1	橙色	DATA+	1
2	n.c.		2	n.c.		2
3	蓝色	DATA-	3	蓝色	DATA-	3
4	屏蔽		4	屏蔽		4



技术参数

额定电压	[V]	60
额定电流	[A]	4
接触电阻		≤5mΩ
插针材料		CuSn
插针表面材料		Ni/Au
插头材料		TPU,阻燃性高,具自熄灭性质
防护等级		IP65/IP67/IP69K
温度参数		
针式/孔式	[°C]	-25 ... 90

订货数据

	型号	订货号
0.3m	PA-MRA-FRA-8BA/L0003	3329240003
0.5m	PA-MRA-FRA-8BA/L0005	3329240005
1m	PA-MRA-FRA-8BA/L0010	3329240010
2m	PA-MRA-FRA-8BA/L0020	3329240020
5m	PA-MRA-FRA-8BA/L0050	3329240050
10m	PA-MRA-FRA-8BA/L0100	3329240100
15m	PA-MRA-FRA-8BA/L0150	3329240150
20m	PA-MRA-FRA-8BA/L0200	3329240200
可订制	PA-MRA-FRA-8BA/L0000	3329240000

信号指示、线路分配

M12	线芯颜色	信号	M12
1	橙色	DATA+	1
2	n.c.		2
3	蓝色	DATA-	3
4	屏蔽		4