


M8 Y型分支器
M8 Y-Splitter, Male-2*Female



技术参数/Technical data

适用温度/Ambient temperature	-20°C ~ +80°C
胶芯材料/Connector insert	TPU/PA+GF
端子材料/Connector contacts	黄铜镀金/Brass with gold plated
螺丝/螺母材料/Connector nut/screw	锌合金镀镍/Brass with nickel plated
密封材料/Seal	氟橡胶(FKM)
内模材料/Innermold	≥100MΩ
外模材料/Overmold	≤5mΩ
绝缘阻抗/Insulation resistance	否/Unavailable
接触阻抗/Contact resistance	参照P36
是否屏蔽/Shielding or not	>500次/Cycles
钻孔尺寸/Panel cut-out	A;B
插拔次数/Mating endurance	
接口防呆类型/Coding	




订货信息/Ordering information

芯数/Contacts	接线表/Wire list	额定电流/Rated current	额定电压/Voltage		型号/model
			交流(A/C)	直流(D/C)	
<p>(公头) (母头)</p>	<p>公头: 1 3 4 母头(1): 4 3 1 母头(2): 1 3 4</p>	3A	50V	60V	F11Y3P
<p>(公头) (母头)</p>	<p>公头: 1 2 3 4 母头(1): 4 3 2 1 母头(2): 1 2 3 4</p>	3A	50V	60V	F11Y4P
<p>(公头) (母头)</p>	<p>公头: 1 2 3 4 5 母头(1): 5 4 3 2 1 母头(2): 1 2 3 4 5</p>	3A	30V	30V	F11Y5P

M8 L型转换器
M8 L-Adapter, Male-Female

技术参数/Technical data

执行标准/Execution standard	IEC 61076-2-104
适用温度/Ambient temperature	-20°C ~ +80°C
胶芯材料/Connector insert	TPU/PA
端子材料/Connector contacts	黄铜镀金/Brass with gold plated
外模材料/Overmold	TPU
螺丝/螺母材料/Connector nut/screw	锌合金镀镍/Zinc alloy with nickel plated
密封材料/密封圈/Seal/O-ring	氟橡胶(FKM)
绝缘阻抗/Insulation resistance	≥100MΩ
接触阻抗/Contact resistance	≤5mΩ
是否屏蔽/Shielding or not	否/Unavailable
插拔次数/Mating endurance	>500次/Cycles
接口防呆类型/Coding	A;B


订货信息/Ordering information

芯数/Contacts	接线表/ Wire list	额定电流/ Rated current	额定电压/Voltage		型号/model
			交流(A/C)	直流(D/C)	
 (公头) (母头)	公头 母头 1 _____ 1 2 _____ 2 3 _____ 3	3A	50V	60V	F11L3P
 (公头) (母头)	公头 母头 1 _____ 1 2 _____ 2 3 _____ 3 4 _____ 4	3A	50V	60V	F11L4P
 (公头) (母头)	公头 母头 1 _____ 1 2 _____ 2 3 _____ 3 4 _____ 4 5 _____ 5	3A	30V	30V	F11L5P